

Garage and MOT Test Equipment Consultants & Suppliers



LUCAS AIDE GEMS

Garage Equipment Money Savers

www.gems.me.uk

Quotation

GEMS – 'Tufflor' Floor Paint

"Our toughest, strongest, most durable epoxy Floor coating

Excellent resistance to dilute acids, dilute alkalis, oil, petrol, diesel, vegetable oils, raw sewage etc

Description

GEMS-Tufflor is a two pack **Solvent Free** Epoxy coating which provides protective and decorative properties to concrete, steel and other substrates.

The material is supplied as a two pack system, comprising pre-weighed amounts of BASE and CURING AGENT. After mixing together, an easily applied chemical and abrasion resistant finish is produced.

Typical Uses

As a tough, waterproof wear resistant floor coating for Car & Commercial Vehicle Garage Floors, Manufacturing areas, Showroom, Trafficked Warehouse areas, Food preparation areas, Factory floors, Brewery Floors, Abattoir- Industrial and Domestic, Bottling factories, Engineering workshop floors, Aircraft hangar etc.

Suitable for Interior or Exterior projects.- Concrete, Steel and other substrates

Advantages

- Solvent free, low odour
- Very good chemical resistance
- Excellent adhesion to concrete
- High build

Lucasaide Ltd., Unit 1E, Chelston Enterprise Centre,
Castle Road, Wellington, Somerset. TA21 9JQ
Tel: 01823 617 900, Fax: 01823 617 900
www.gems.me.uk www.lucasaide.com
www.garageequipmentmoneysavers.com

E-mail: sales@garageequipmentmoneysavers.uk

- **Tough and durable**
- **Easily applied**
- **Hygienic and easily cleaned**

Typical Properties

Pot life @ 20°C: 45 Minutes

@ 10°C: 90 Minutes

Colours: Red Cherry 04D45, Blue Sky RAL 5015, Auto Blue 20E51, Silver Grey RAL 7001, Iron Grey RAL 7011, Auto Grey 10A07, Leaf Green RAL 6002, Oxide Red RAL 3009, Safety Yellow, Black, White

[Click to download a colour chart](#)



Coverage: 0.25-0.30kg/m²/coat

Tack free time @ 20°C: 6 hours

Hard dry time @ 20°C: 10 hours

Full chemical resistance @ 20°C: 7 days

Adhesion strength to concrete: 3.9 MPa (concrete failure)

Adhesion strength to mild steel: >12 MPa

Chemical resistance: excellent resistance to dilute acids, dilute alkalis, oil, petrol, diesel, vegetable oils, raw sewage etc

Packaging

GEMS Tufflor is supplied in **5kg** packs

GEMS Tufflor is also supplied in **15kg** packs in three colours only:-
Auto Blue 20E51, **Auto Grey 10A07** and **Silver Grey RAL7001**

Coverage

A 5kg pack is sufficient to treat 16/20 m² of surface area per Coat

PRICE LIST

1 x 5kg -GEMS FLORPRIME (Primer) @ £ 78.00 ea + vat

1 x 5kg – GEMSTUFLOR TOP COAT @ £ 88.00 ea + vat

1 x APPLICATION KIT with ROLLERS @ £68.00 ea + vat

Lucasaide Ltd.,, Unit 1E, Chelston Enterprise Centre,
Castle Road, Wellington, Somerset. TA21 9JQ
Tel: 01823 617 900, Fax: 01823 617 900
www.gems.me.uk www.lucasaide.com
www.garageequipmentmoneysavers.com

E-mail: sales@garageequipmentmoneysavers.uk

**CHEVRON HAZARD- SAFETY(YELLOW/BLACK) –
FLOOR PAINT MARKING KIT**

Recommended Kit items :-

- (1) 1 x 5kg GEMS Florprime (Primer) @ £ 78.00 + vat**
- (2) 1 x 5kg GEMS TUFLOR TOP COAT
- SAFETY YELLOW @ £ 88.00 + vat**
- (3) 1 x 5kg GEMS TUFLOR TOP COAT
BLACK @ £ 88.00 + vat**
- (4) Application Kit with Roller @ £ 68.00 + vat**
- (5) Carriage (UK) @ £ 40.00 + vat**

Note Kit does not contain Templates

Total Kit Price £ 462.00 + vat



Lucasaide Ltd.,, Unit 1E, Chelston Enterprise Centre,
Castle Road, Wellington, Somerset. TA21 9JQ
Tel: 01823 617 900, Fax: 01823 617 900
www.gems.me.uk www.lucasaide.com
www.garageequipmentmoneysavers.com

E-mail: sales@garageequipmentmoneysavers.uk

COLOUR CHART



Red Cherry 04D45



Blue Sky RAL5015



Auto Blue 20E51



Silver Grey RAL 7001



Iron Grey RAL7011



Auto Grey 10A07



Leaf Green RAL6002



Oxide Red RAL3009



Safety Yellow



Black

Colours are to the British Standard or German RAL specification. Printed Sheets and monitor screens can distort the colours. White is also available.